

# U.S. INDUSTRIAL MACHINERY, INC.

P.O. BOX 2098                      MEMPHIS, TN 38101  
PHONE: (800) 932-8376    FAX: (901) 526-2339

Visit Our Web Site at [www.usindustrial.com](http://www.usindustrial.com)

Gentleman:

We are pleased to offer for your consideration:

## **ONE (1) U.S. INDUSTRIAL 26X80 PRECISION ENGINE LATHE**

Model Number: US 2680 CZ

This Precision, Heavy Duty Engine Lathe incorporates hardened and precision ground bed ways on longitudinal and cross ways, and wide, precision-ground gears thru ought. It is gap-bed design, has feed-rod/lead screw safety interlock system, weight bearing tail stock, forward-reverse levers at both the aprons and the headstock. As with all U.S. Industrial lathes, it comes with a full complement of standard accessories, 3 and 4 Jaw Chucks, Follower and Steady Rests, Taper Attachment, Coolant System, 4-Way Rapid Traverse, Operator/Splash Protection, Work Lamp, "T" Slot Compound, Change Gears, Operator/Svc. Manual.

### **SPECIFICATIONS:**

Swing over bed	25.98"
Swing over Carriage	15.16"
Swing over Gap	33.85"
Gap Length	11.8
Width of bed	19.29"
Spindle Bore	4.134"
Spindle Type	D-11 Camlock
Speeds, No./Range	18/14-900rpm
Feeds: Long./Cross	72 kinds
Inch Threads, No./Range	048-22.8/.016-7.6
Metric Threads, No./Range	37 kinds/1-28 t.p.i.
Diametrial Threads, No./Range	54 kinds/1-240mm
Module Threads, No./Range	27 kinds/1-30 t.p.i.
Cross-slide Travel	45 kinds/0.5-60 DP
Tool Compound Travel	15.75"
Tail-stock Taper	9.06"
Tail-stock Spindle Travel	Mt 5 or 6
Tail-stock Spindle Diameter	8.07"
Main Motor HP	3.94"
	20 HP (220/440V)

Rapid Feed Motor	1/6 HP
Coolant Pump Motor	1/8 HP
Lathe Net Weight	11,000 lbs.

**PRICE.....F.O.B. MEMPHIS.....\$24,990.00**

**AVAILABLE OPTIONS:**

Taper Attachment	\$ 1,500.00
------------------	-------------

We await your reply and thank you for this opportunity to quote.

Sincerely,  
U. S. INDUSTRIAL MACHINERY, INC.