

U.S. INDUSTRIAL MACHINERY

HYDRAULIC IRONWORKERS



Equipment for the American Industry
120 Webster Ave. Memphis, TN 38126
800-860-1850 Fax: 901-526-2339

MODEL	USHI-66-DO	USHI-90-DO	USHI-125-DO	USHI-155-DO
PUNCH				
PUNCH TONNAGE	66	90	125	155
PUNCHING THICKNESS	5/8"	3/4"	1"	1 1/4"
PUNCHING DIAMETER	1 1/4"	1 1/4"	1 1/2"	1 1/2"
THROAT DEPTH	12"	14"	16"	24"
STROKE LENGTH	0-3 1/8"	0-3 1/8"	0-3 1/8"	0-3 1/8"
FLAT BAR SHEAR				
MAX. THICKNESS	12" x 5/8"	14" x 3/4"	14" x 1"	14" x 1 1/4"
MAX. LENGTH	16" x 5/16"	18" x 5/8"	24" x 5/8"	24" x 3/4"
BLADE LENGTH	16"	19"	24"	24"
ANGLE SHEAR				
CAPACITY 90 DEGREES	5" x 5" x 3/8"	6" x 6" x 1/2"	6" x 6" x 5/8"	7" x 7" x 5/8"
CAPACITY 45 DEGREES	2" x 2" x 1/4"	2" x 2" x 3/8"	3 x 3 x 1/4"	3 x 3 x 5/16"
BAR SHEAR				
ROUND	1 3/4"	2"	2 3/8"	2 1/2"
SQUARE	1 5/8"	2"	2 1/8"	2 1/8"
NOTCHER				
THICKNESS	3/8"	1/2"	1/2"	5/8"
WIDTH	2 1/4"	2 1/4"	2 1/4"	2 3/8"
DEPTH	4"	4"	4"	4"
MOTOR	7.5 HP	10 HP	15 HP	20 HP
WEIGHT	3527 LBS	5260 LBS	10,560 LBS	14960 LBS
L X W X H	64"x28"x69"	73"x35"x74"	92"x37"x82"	105"x40"x90"
OIL CAPACITY	20 GAL	25 GAL	33 GAL	64 GAL

Disclaimer: All items listed on this brochure are subject to change without notice.



Equipment for the American Industry
120 Webster Ave. Memphis, TN 38126
800-860-1850 Fax: 901-526-2339