

U.S. INDUSTRIAL MACHINERY

P.O. BOX 2098

MEMPHIS, TN 38101

PHONE: (800) 860-1850

FAX: (901) 526-2339

Visit Our Web Site at www.usindustrial.com

Dear Customer:

We are pleased to offer for your consideration:

ONE (1) NEW U.S. INDUSTRIAL 26" X 120" PRECISION GEARED HEAD ENGINE LATHE MODEL USL26X120BH-KIT

This precision, **heavy duty geared head engine lathe** incorporates hardened and precision ground bedways on longitudinal and cross ways, and wide, precision ground gears. It has a gap-bed design, feed-rod/lead screw safety interlock system, weight bearing tailstock and forward/reverse levers at both the aprons and the head stock.

As with all U.S. Industrial lathes, it comes with a plethora of standard accessories, 3 and 4-jaw chucks, follower and steady rests, 4-way rapid travel, work lamp, a coolant system and an operator/service manual.

Standard Equipment: (Items below are INCLUDED with the machine)

- 12" 3-jaw chuck. Universal, self-centering with an American standard tongue and groove top Jaws.
- 16" 4-jaw independent chuck
- Steady rest
- 4-way toolpost
- Thread Dial
- Work lamp
- Flood coolant system
- Sino 2-axis digital readout inch/metric ***(installed)***
- Inch reading dials on Apron, Cross-Slide and compound
- Manual with test certificate
- 25" Face Plate & Dog Plate
- Foot brake with microswitch and brake
- Follow rest
- 4-way rapid travel
- Safety chuck shield
- Taper attachment ***(installed)***
- Large spindle bore to pass 4"
- Traveling Backsplash Behind Apron
- Slide out chip pans



*** continued on Page 2 ***

July17

U.S. INDUSTRIAL MACHINERY

P.O. BOX 2098 MEMPHIS, TN 38101
 PHONE: (800) 860-1850 FAX: (901) 526-2339
 Visit Our Web Site at www.usindustrial.com

Specifications and important information:

Swing Over Bed	26" (660mm)
Swing Over Cross-Slide	16.53" (420mm)
Swing Over Gap	34.25" (870mm)
Gap Length	9.44" (240mm)
Maximum Workpiece Length with 3-jaw chuck	118" (3000mm)
Maximum Turning Length	116" (2950mm)
Spindle Bore	4.134" (105mm)
Spindle Type	D1-8 Camlock
12 Spindle Speeds	36 to 1600 RPM
65 Longitudinal Feeds	.0023 to .0937 IPR
65 Cross Feeds	.0011 to .0404 IPR
22 Metric Threads	1 to 14mm
2 Inch Threads	2 to 28 TPI
18 Module Threads	0.5 to 7mm
24 Diametral Pitch Threads	4 to 56 DP
Compound Rest Travel	5.75"
Cross-Slide Travel	12.125"
Tailstock Taper	No. 5 Morse Taper
Tailstock Spindle Travel	5.906" (150mm)
Tailstock Spindle Diameter	2.953" (75mm)
Main Motor HP	10 HP (7 kw) 220V or 440V, 3-Phase
Rapid Feed Motor	0.4 HP
Coolant Pump Motor	.16 HP, 11 gallons per minute
Lathe Gross Weight	8,500 lbs.
Dimensions	183" long, 40" wide, 55" tall

PRICE.....F.O.B. MEMPHIS.....\$29,990.00

Standard Accessories
included with Lathe.

*** continued on Page 3 ***




U.S. INDUSTRIAL MACHINERY


P.O. BOX 2098
PHONE: (800) 860-1850

MEMPHIS, TN 38101
FAX: (901) 526-2339


Visit Our Web Site at www.usindustrial.com



Detail of Headstock



Apron with travelling digital readout display, follow rest, steady rest, taper attachment, rapid travels.



View from back of lathe shows travelling backslash.

AVAILABLE OPTIONS:

- | | |
|---|-------------------|
| Quick Change Toolpost Kit with Holders..... | \$1,495.00 |
| ISO Cutting Tool Package..... | \$2,695.00 |

We await your reply and thank you for this opportunity to quote.

Sincerely,

U.S. INDUSTRIAL MACHINERY, INC.

July17