

# U.S. INDUSTRIAL MACHINERY

P.O. BOX 2098

MEMPHIS, TN 38101

PHONE: (800) 860-1850

FAX: (901) 526-2339

Visit Our Website at [www.usindustrial.com](http://www.usindustrial.com)

Dear Customer,

We are pleased to offer for your consideration:

**ONE (1) NEW U.S. INDUSTRIAL 250 TON X 13'  
HYDRAULIC PRESS BRAKE, 3-AXIS CNC,  
(with CNC Autocrown bed and X, Y and R Axis)**

Model Number: USHB250-13CNC



## STANDARD EQUIPMENT: (All of the following comes with the machine)

- Ram Deflection Adjustment
- Massive Torsion Bar for Parallelism
- Three Speed Ram
- Bottom Time Delay
- Inching, Single Cycle and Auto Run
- Bed tools are held with standard slot for 1/2" x 5/8" tang w/set screws, plus die clamps are included
- Ram takes standard American Tang Tooling (1/2" x 5/8") and American Safety Tang Tooling, and Z1
- Space between Ram Tool Clamps allows for deep box bending
- Free Gooseneck Punch and multi-opening Die for up to 90° forming up to 10-gauge mild steel  
(See note on page 2)
- Setting for ram speed slowdown and return position
- Forged Heavy Duty Cylinder and Cylinder Body
- Rapid Approach, Bending Cycle and Rapid Retreat
- All Steel Construction

## SPECIFICATIONS:

• Working Pressure:	250 Tons	• Rapid Ram Travel Speed:	2.4"/sec.
• Length of Working Table:	157.4"	• Rapid Ram Retreat Speed:	2.0"/sec.
• Distance Between Housings:	124"	• Pressing Speed:	Dependent on Tool Load
• Throat Depth:	15.7"	• Hydraulic Oil Capacity:	108 Gal.
• Back Gauge Travel:	23.5"	• Motor Horsepower:	25 HP, 220 or 440 Volt, 3 ph.
• Stroke Adjustment of Ram:	3.14"	• Net Weight:	39,683 lbs.
• Ram Travel:	7.8"	• Length:	179"
• Open Height:	22"	• Width:	75"
• Strokes per Minute:	5	• Height:	108"
• Backgauge Travel:	24"		

\*specifications are subject to change without notice

\*\*\* Continued on Page 2 \*\*\*

**IMPORTANT FEATURES INCLUDED WITH U.S. INDUSTRIAL PRESS BRAKES:**






- **Special Note:** The Gooseneck Punch and multi-opening Die included are general purpose tools to be used for training. Precision tooling should be purchased to meet your specific needs. The punch is segmented and it is up to the customer to calibrate these if they want to use them for a particular purpose.  
\* **There is no warranty on this tooling.**



Gooseneck Punch Tool Sections included, full length of Ram. Multi-opening V-Die for up to 90 degree forming included, full length of bed. Die lifting rings included.

Our **bed** has slot for the Standard Die Tang as shown below. Also, bed tooling without tang can be held with the included capture clamps.

**Our Standard Ram Clamps and Optional cam-lever Ram Clamps will hold all Punch Tangs shown below:**



Our **standard** ram clamp for all punch tangs above, two allen-head cap screws to secure tools.

Our **optional** ram clamps for all punch tangs shown above. Lever action allows for quick tool change.



\*\*\* Continued on Page 3 \*\*\*

<b>PRICE..... F.O.B. MEMPHIS</b>	<b>\$ 79,990.00</b>
<b>CNC 2-axis Color Graphic Computer Control</b>	<b>4,995.00</b>
<b>Sick deTec 4 Light Curtain</b>	<b>4,990.00</b>
<b>Third Axis (Back Gauge Height controlled from operator panel.)</b>	<b>4,995.00</b>
<b>CNC Controlled Mechanical Auto Crown</b>	<b><u>9,995.00</u></b>

**TOTAL – Normal stock or short delivery** **F.O.B. MEMPHIS \$ 104,965.00**

**AVAILABLE OPTIONS:**

- **CNC 2-Axis Color Graphic Control:** Shown above  
 Controls BOTH Bend Angle and Backgauge Position. Comes with 6" LCD touch screen. Code and Graphic programming included. Graphic allows 10 bends per program/cross-section. Controls features a tool library, Metric/inch switchable, Auto bend sequence, Auto retract of Backgauge, Spread length, Interference bend alert, Calculated bend allowance, Programmable ram dwell and much more. Control stores thousands of programs with USB Port, Ethernet and RS232 for program backup.
- **Sick Model deTec 4 Light Curtain System – Minimum OSHA Requirement** Shown above
- **Upgrade to Fiessler Akas II Laser Guarding (Substitute for Sick deTec 4)** \$7,995.00
- **Upgrade to Pilz PSEnvip LED Safety Guarding: (Substitute for deTec 4)** \$8,495.00
- **Add Third Axis (Back Gauge Height controlled from operator panel.)** Shown above
- **CNC Controlled Mechanical Auto Crown** Shown above
- **Upgrade to Cam-Lever Quick Action Ram Clamps** \$6,495.00
- **High Speed Servo Back Gauge** \$4,995.00
- **Training in our Memphis, TN Facility** No Charge
- **Training at customer site, less than 300 miles from Memphis:** \$2,995.00
- **Training at customer site, more than 300 miles from Memphis:** \$3,995.00  
 (If outside continental USA, please call for quote.)

***Press Brake CNC operators panel with LCD touch screen and graphics function***



We await your reply and thank you for this opportunity to quote

**U.S. INDUSTRIAL MACHINERY**