U.S. INDUSTRIAL MACHINERY

P.O. BOX 2098 MEMPHIS, TN 38101 PHONE: (800) 860-1850 FAX: (901) 526-2339 Visit Our Website at www.usindustrial.com

Dear Customer,

We are pleased to offer for your consideration:

ONE (1) NEW U.S. INDUSTRIAL 155 TON X 8' **HYDRAULIC PRESS BRAKE with manual controls** Model Number: USHB155-8HM

FRONT OPERATED POWER BACKGAUGE, POWER RAM ADJUST, MANUAL FINE ADJUST HANDWHEELS and DIGITAL POSTION DISPLAYS

STANDARD EQUIPMENT: (All of the following comes with the machine)

- Power Front Operated Back Gauge, motorized with fine adjustment handwheel Digital Display shows Backguage position in .001"
- Power Ram Depth Control, motorized with fine adjustment handwheel Digital Displays shows Ram position in .001"
- Ram Deflection Adjustment
- Massive Torsion Bar for Parallelism
- Three Speed Ram
- Bottom Time Delav
- Inching and Single Cycle
- Ram takes standard American Tang Tooling (1/2" x 5/8") and American Safety Tang Tooling, and Z1 Space between Ram Tool Clamps allows for deep box bending
- Free Gooseneck Punch and multi-opening Die for up to 90° forming up to 10-gauge mild steel (see note on page 2)

SPECIFICATIONS:

• Working Pressure:

*** Continued on Page 2 ***

- Length of Working Table:
- Distance Between Housings:
- Throat Depth: Stroke Adjustment of Ram:
- Ram Travel:
- Open Height: 16.3"
- Rapid Ram Travel Speed: 2.4"/sec.
- Rapid Ram Retreat Speed: 2.0"/sec. 24"
- Backgauge Travel:

- Setting for ram speed slowdown and return position
- Forged Heavy Duty Cylinder and Body
- Rapid Approach, Bending and Rapid Retreat
- All Steel Construction
- Bed tools are held with standard slot for 1/2" x 5/8" tang w/set screws, plus die clamps are included

155 Tons

5.9"

 Hydraulic Oil Capacity: 98.4" 80.7" • Motor Horsepower: 12.5" • Net Weight: 2.36" • Length:

Pressing Speed:

- Width: • Height:

Dependent on Tool Load 60 Gal. 10 HP, 220 or 440 Volts, 3 ph. 45/22.5 amps 17,640 lbs. 120" 64" 101"

U.S. MUSI

IMPORTANT FEATURES INCLUDED WITH U.S. INDUSTRIAL PRESS BRAKES:


- **Special Note:** The Gooseneck Punch and multi-opening Die included are general purpose tools to be used for training. Precision tooling should be purchased to meet your specific needs. The punch is segmented and it is up to the customer to calibrate these if they want to use them for a particular purpose.
- * There is no warranty on this tooling.





Gooseneck Punch Tool Sections included, full length of Ram. Multiopening V-Die for up to 90 degree forming included, full length of bed. Die lifting rings included.


Our **bed** has slot for the Standard Die Tang as shown below. Also, bed tooling without tang can be held with the included capture clamps.

Our Standard Ram Clamps and Optional cam-lever Ram Clamps will hold all Punch Tangs shown below:











Our **standard** ram clamp for all punch tangs above, two allenhead cap screws to secure tools.

> Our **optional** ram clamps for all punch Tangs shown above. Lever action allows for quick tool change.



*** Continued on Page 3 ***

AVAILABLE OPTIONS:

- Sick Model deTec 4 Light Curtain System Minimum OSHA Requirement
- Upgrade to Fiessler Akas II Laser Guarding (Substitute for Sick deTec 4)
- Upgrade to Pilz PSENvip LED Safety Guarding: (Substitute for deTec 4)
- Manual (hand-crank) Mechanical Bed Crowning Device
- Upgrade to Cam-Lever Quick Action Ram Clamps
- Training in our Memphis, TN Facility
- Training at customer site, less than 300 miles from Memphis:
- Training at customer site, more than 300 miles from Memphis:
- (If outside continental USA, please call for quote.)



Photos above are manual Hydraulic Press Brake with front-operated power backgauge, power ram adjustment, both with manual fine adjustment and digital readouts. Operator's pendant has dwell adjustment for ram, key lockout, jog control and E-stop.

We await your reply and thank you for this opportunity to quote.

U.S. INDUSTRIAL MACHINERY

Page 3 of 3