

Visit Our Web Site at www.usindustrial.com

## ONE (1) NEW U.S. INDUSTRIAL 16" X 40" PRECISION GEARED HEAD ENGINE LATHE MODEL USL1640 Spindle bore will pass 3"

This precision, **heavy duty geared head engine lathe** incorporates hardened and precision ground bedways on longitudinal and cross ways, and wide, precision ground gears. It has a gap-bed design, feed-rod/lead screw safety interlock system, weight bearing tailstock and forward/reverse levers at both the aprons and the head stock.

As with all U.S. Industrial lathes, it comes with a plethora of standard accessories, 3 and 4-jaw chucks, follower and steady rests, work lamp, a coolant system and an operator/service manual.

#### Standard Equipment: (Items below are INCLUDED with the machine)

- 10" 3-jaw Chuck. Universal, Self-centering
- 12" 4-Jaw Independent Chuck
- Steady Rest
- 4-Way Toolpost
- · Micrometer Carriage Stop
- Thread Dial
- Work Lamp
- · Flood Coolant System
- Sino 2-axis digital readout inch/metric (installed)

- 15" Face Plate & Dog Plate
- · Foot Brake with microswitch
- Follow Rest
- · Safety Chuck Shield
- Taper Attachment (installed)
- · Large Spindle Bore to pass 3"
- Full Length Backsplash
- Slide-out Chip Pan
- · Manual with test certificate

 Inch/metric Reading Dials on Apron, Cross-Slide and Compound

U.S.



## **INDUSTRIAL MACHINERY**

P.O. BOX 2098

PHONE: (800) 860-1850

MEMPHIS, TN 38101

FAX: (901) 526-2339 Visit

Our Web Site at www.usindustrial.com

### **Specifications and important information:**

Swing Over Bed

Swing Over Cross-Slide

Swing Over Gap

Gap Length

Maximum Workpiece Length

Spindle Bore

Spindle Type

15 Spindle Speeds

66 Longitudinal Feeds

66 Cross Feeds

66 Metric Threads

66 Inch Threads

33 Module Threads

33 Diametral Pitch Threads

Compound Rest Travel Cross-Slide Travel Tailstock Taper

Tailstock Spindle Travel

Main Motor HP

Coolant Pump Motor Lathe Gross Weight

**Dimensions** 

16.53" (420mm)

8.85" (225mm) 21.65" (550mm)

10.23" (260mm)

39.37" (1000mm)

3.15" (80mm)

D1-8 Camlock

24 to 1600 RPM

.0027 to .15 IPR .00135 to .075 IPR

0.5 to 28mm

1 to 56 TPI

0.5 to 3.5mm 8 to 56

DP

5.119" (130mm) 12" (305mm)

No. 5 Morse Taper

4.72" (120mm)

10 HP (7.5 kw) 220V or 440V, 3-Phase Fractional HP 3.900

lbs.

100" long, 48" wide, 60" tall

### **AVAILABLE OPTIONS:**

Quick Change Toolpost Kit with Holders......

ISO Cutting Tool Package.....

(QCTP13-16) (ISOSET16)

We await your reply and thank you for this opportunity to quote.

Sincerely,

U.S. INDUSTRIAL MACHINERY

October 2022

## **U.S. INDUSTRIAL MACHINERY**

P.O. BOX 2098 MEMPHIS, TN 38101 PHONE: (800) 860-1850 FAX: (901) 526-2339 **Visit Our Web Site at www.usindustrial.com** 

Detail of Headstock, chuck and guard

Detail of Apron, digital readout and tailstock





### QUICK CHANGE TOOLPOST OPTION - (Replaces standard four-way toolpost

Thank you for the opportunity to quote. We are pleased to offer the following equipment for your consideration:


# ONE – NEW QUICK CHANGE TOOLPOST WITH FIVE HOLDERS, FOR FACTORY ONLY INSTALL ON USL SERIES LATHES

Note: We use the wedge style, #333 for our Lathes. This comes with Part off holder, knurling holder, boring bar holder, and two 3/4" SS holders

This is custom installation AND not available after machine ships. Must be installed on lathe at time of order, prior to shipping.

Extra holders





### **Cutting Tool Package for U.S. Industrial Lathes:**

This optional cutting tool package is designed to fit our QUICK CHANGE TOOLPOST option. It is not for the standard 4-way toolpost.

#### Tools included below are for:

- · Rough and medium finishing of the part OD. Fine finish of the part ID
- Left- and right-hand tools for working left and right hand shoulders
- Tools for threading OD and ID
   Tools for boring the ID
- Part off tools And more......

List of carbide cutting tools in KIT for US INDUSTRIAL LATHE: (ISO tools are imports.)	
Note: Tools for 13", 16", 20" and 26" Lathes will be ¾" square shank  Note: Customer MUST purchase option, OUR QC Toolpost set for install prior to shipping:	
Note: Customer MOST purchase option, OON QC Toolpost set for install prior to shipping.	
<ol> <li>MW LN-R, ¾" square, triangle insert, right hand</li> <li>MW LN-L, ¾" square, triangle insert, left hand</li> <li>Box of 10 W NMG inserts for above</li> </ol>	
4. MCLN-R, ¾" square, diamond insert, right hand	
7. MVJN-R, ¾" square, diamond insert, fine finish, right hand	
10. SER-0750-SET, ¾" square, for threading OD, with inserts (This is a KIT and includes threading inserts.)	
11.SIR-0750-SET, ¾" round, for threading ID, with inserts (This is a KIT and includes threading inserts.)	
12. SCLCR-SET, Boring bars, .315", 3/8", ½", 5/8", ¾" bars, with inserts (This is a KIT and includes inserts.)	
13. RH-MCLN, Boring bar, 1" diameter, 12" long	
15. HSS Blade for part-off holder, high speed steel Block, blade an 10 self-lock carbide parting/grooving inserts	ıd
16. Arbor and key chuck for tailstock	