

Visit Our Web Site at www.usindustrial.com

ONE (1) NEW U.S. INDUSTRIAL 20" X 120" PRECISION GEARED HEAD ENGINE LATHE MODEL USL20120 Spindle bore will pass 4"

This precision, **heavy duty geared head engine lathe** incorporates hardened and precision ground bedways on longitudinal and cross ways, and wide, precision ground gears. It has a gap-bed design, feed-rod/lead screw safety interlock system, weight bearing tailstock and forward/reverse levers at both the aprons and the head stock.

As with all U.S. Industrial lathes, it comes with a plethora of standard accessories, 3 and 4-jaw chucks, follower and steady rests, 4-way rapid travel, work lamp, a coolant system and an operator/service manual.

Standard Equipment: (Items below are INCLUDED with the machine)

• 12" 3-Jaw Chuck. Universal, Self-centering





- 16" 4-Jaw Independent Chuck
- Steady Rest
- 4-way Toolpost
- Thread Dial
- Work Lamp
- Flood Coolant System
- Sino 2-Axis Digital Readout inch/metric (installed)
- Inch Reading Dials on Apron, Cross-Slide and

- · Manual with test certificate
- 25" Face Plate & Dog Plate
- Foot Brake with Microswitch
- Follow Rest
- 4-Way Rapid Travel Safety Chuck Shield
- Taper Attachment (installed)
- · Large Spindle Bore to pass 4"
- Traveling Backsplash Behind Apron
- Slide Out Chip Pan

U.S. INDUSTRIAL MACHINERY

P.O. BOX 2098 MEMPHIS, TN 38101 PHONE: (800) 860-1850 FAX: (901) 526-2339

Visit Our Web Site at www.usindustrial.com

Specifications and important information:

Swing Over Bed

Swing Over Cross-Slide 19.7" (500mm)
Swing Over Gap 11.8" (300mm) 28"

Gap Length (710mm)

Maximum Workpiece Length with 3jaw 9.44" (240mm) chuck 118" (3000mm)

Maximum Turning Length116" (2950mm)Spindle Bore4.134" (105mm)Spindle TypeD1-8 Camlock12 Spindle Speeds36 to 1600 RPM65 Longitudinal Feeds.0023 to .0937 IPR

65 Cross Feeds .0011 to .0404 IPR
22 Metric Threads 1 to 14mm
27 Inch Threads 2 to 28 TRI

27 inch Threads
2 to 28 TPI
18 Module Threads
0.5 to 7mm 4 to

24 Diametral Pitch Threads 56 DP
Compound Rest Travel 5.75"
Cross-Slide Travel 12.125"

Tailstock Taper No. 5 Morse Taper

Tailstock Spindle Travel

5.906" (150mm)

Tailstock Spindle Diameter

2.953" (75mm)

Main Motor HP

10 HP (7 kw) 220V or 440V, 3-Phase

Rapid Feed Motor

0.4 HP

Coolant Pump Motor

.16 HP, 11 gallons per minute 7,700

Lathe Gross Weight

lbs.

Dimensions

183" long, 40" wide, 50" tall

Order Model Number: USL20120 AVAILABLE

OPTIONS:

We await your reply and thank you for this opportunity to quote.

Sincerely,

U.S. Industrial Machinery

U.S. INDUSTRIAL MACHINERY

P.O. BOX 2098

MEMPHIS, TN 38101

PHONE: (800) 860-1850

FAX: (901) 526-2339 Visit

Our Web Site at www.usindustrial.com


U.S. INDUSTRIAL 20" X 120" PRECISION ENGINE LATHE | Model Number: USL20X120BH-KIT






Also includes steady rest, follow rest, 3-jaw chuck, and 2-axis DRO See pic on Page 1.

Apron with travelling digital readout display, follow rest, steady rest, taper attachment, rapid travels.





QUICK CHANGE TOOLPOST OPTION – (Replaces standard four-way toolpost)

Thank you for the opportunity to quote. We are pleased to offer the following equipment for your consideration:


Cutting Tool Package for U.S. Industrial Lathes: ONE – NEW QUICK CHANGE TOOLPOST WITH FIVE HOLDERS, FOR FACTORY ONLY INSTALL ON USL SERIES LATHES

This optional cutting tool package is designed to fit our QUCIK CHANGE TOOLPOST option. It is not for the standard 4-way toolpost.

Tools included below are for: Wedge style Kit, #444 fo r our Lathes for 1" Square tools. This comes with Part off holder, knurling holder, boring bar holder, and two 1" SS holders

5. MCLN-L, 3/4" square, diamond insert, left hand.....

6. Box of 10 CNMG inserts for above.....



7. MVJN-R, ¾" square, diamond insert, fine finish, righ

(T•hi sLeft ship- and rights only in-hand tools for working left and right hand shouldersstalled on lathe.)

• Tools for threading OD and ID

Tools for boring the ID

Thi. s iPart off toolss custom i

nstallation AND not

available after machine shiAnd more.....ps.

Must be installed on lathe at time of order, prior to shipping.

List of carbide cutting tools in KIT for US INDUSTRIAL LATHE: (ISO tools are imports.)

ExNotra tehol: Toolderss faore $\ r \ 13",75 \ 16.0"0, 20"$ and 26" Lathes each. will be $\ 34"$ square shank

*Myses II much observe QC bust good to bust-on much band observed constraints smoot wanting working tolerances.	ore advanced from provider and provider to make the	8
Quickly and easily religion on an eng- il about thomas QC tool and unto per- troon few precion work to bear and	books a would clange of payer-strains.	
All party are hardened, pround and or maintenance free operation.	maintely seried for	
Handouse rigidity for chemic free part	weens.	
Pliane II good charge QC tool post to ordetry leading brands he serve."	to and international sector all	
EACH STYLE, WE A 2 AND U	POST AND S HOLDERS, ONE	
PISTON TOOLPIST SETE	NWING	
253-400	2.15	
281-000	10-10"	II
291-000	12.48"	A (40)
251,400	14-30"	Children of the Control of the Contr
WEDGE TOOLPOST SETS		
STOCK #	SWINE.	Charles To Section 1985
281713	9.15	
214-214	11-15	ACC
211 221	17-18"	The second second
273-444	14-25	
241-949	17-12"	
Chairle Channes DC, Zond Freef, Conform No. Charles of Vibration Chairle accept of body - On Dates Out Section Supports (1)	ni.	
	part .	
	Back to Product Listma	

9. Box of 10 VNMG inserts, 1/64" nose radius	
--	--

10. SER-0750-SET, ¾" square, for threading OD, with inserts.....

Cutting Tool Package for U.S. Industrial Lathes:

This optional cutting tool package is designed to fit our QUICK CHANGE TOOLPOST option. It is not for the standard 4-way toolpost.

Tools included below are for:

- Rough and medium finishing of the part OD. Fine finish of the part ID
- · Left- and right-hand tools for working left and right hand shoulders
- Tools for threading OD and ID
 Tools for boring the ID
- Part off tools And more.....

List of carbide cutting tools in KIT for US INDUSTRIAL LATHE: (ISO tools are imports.)

Note: Tools for 20" and 26" Lathes will be 1" square shank

Note: Customer MUST purchase option, OUR QC Toolpost set for install prior to shipping:

- MW LN-R, 1" square, triangle insert, right hand.......
 MW LN-L, 1" square, triangle insert, left hand......
 Box of 10 W NMG inserts for above......
- 4 MCLN-R, 1" square, diamond insert, right hand.....
- 5 MCLN-L, 1" square, diamond insert, left hand......
- 6 Box of 10 CNMG inserts for above.....

.

7	MVJN-R, 1" square, diamond insert, fine finish, right hand	
8	MVJN-L, 1" square, diamond insert, fine finish, left hand	Box of 10
10	. SER-1000-SET, 1" square, for threading OD, with inserts	
	SIR-1000-SET, 1" round, for threading ID, with inserts (This is a Kncludes threading inserts.)	IT and
	SCLCR-SET, Boring bars, .315", 3/8", ½", 5/8", ¾" bars, with inserts (This is a KIT and includes inserts.)	
	RH-MCLN, Boring bar, 1" diameter, 12" long	
	HSS Blade for part-off holder, high speed steel Block, lself-lock carbide parting/grooving inserts	blade and 10
17. L	Arbor and key chuck for tailstock	ni-synthetic